

Push 2 Connect™ Coupler

Push it on. That's it.



BEAD/BABA Approved

- Air Tight - Water Tight
- 350 psi air pass through
- 175 PSI contained
- Push On (DO NOT unscrew caps)

Part Number	Coupler Size	Duct OD	Grip Colors	Box Qty
P2C-1.05	3/4" Smoothwall HDPE	1.05"	Gray	48 or 150
NEW P2C-27MM	27 MM HDPE	1.063"	Orange	55
P2C-1.315	1" Smoothwall HDPE	1.315"	Yellow	85
P2C-1.58	1.25" Smoothwall HDPE True Sized	1.58"	Black	100
P2C-1.66	1.25" Smoothwall HDPE	1.66"	Blue	100
P2C-1.90	1.50" Smoothwall HDPE	1.90"	Red	78
P2C-2.375	2" Smoothwall HDPE	2.375"	Orange	24
P2C-1.66-1.58trans	Transition Coupler 1.25" to 1.25"	1.58" to 1.66"	Black Blue	100

Please Note:

- Loosening collars prior to installing can cause improper installation, create air loss and/or coupler failure.
- Designed for underground use only - NOT UV protected.
- Tape ends if being placed by a blowing machine.



630-584-3321



Steven@r-boc.com or Patrick@r-boc.com



bandctelcomproducts.com



720 N 17th Street, Unit 11, St. Charles, IL 60174