



Push 2 Connect™ Couplers Specification Sheet

Designed for underground use only - Not UV protected



Push it on. That's it.

The DIFFERENCE is CLEAR

Part #	Description	NOM OD	Duct OD Range	End Cap Color	Length	Pull Out Strength	Tested to psi Pass-through	Contained Rating (psi)	Case Qty.
P2C-1.05	0.75" P2C	1.050"	1.040" - 1.080"		4.75"	>550 lbs.	350	175	48 or 150
P2C-27MM	27MM	27MM	26.7mm - 27.7mm		4.75"	>600 lbs.	350	175	55
P2C-1.315	1.00" P2C	1.315"	1.300" - 1.375"		4.75"	>670 lbs.	350	175	85
P2C-1.58	1.25" P2C	1.58"	1.570" - 1.61"		4.88"	>1500 lbs.	350	175	100
P2C-1.66	1.25" P2C	1.66"	1.645" - 1.70"		4.88"	>1500 lbs.	350	175	100
P2C-1.90	1.50" P2C	1.90"	1.885" - 1.925"		4.90"	>1600 lbs.	350	175	78
P2C-2.375	2.00" P2C	2.375"	2.360" - 2.390"		7.75"	>3200 lbs.	350	175	24
P2C-1.66-1.58	1.58/1.66 P2C Transition					See 1.58" and 1.66" specs above.			100

Please Note:

- Loosening collars prior to installing can cause improper installation, create air loss and/or coupler failure.
- Designed for underground use only - NOT UV protected.
- Tape coupler collars if being placed by a blowing machine.
- BEAD/BABA Approved.



630-584-3321

Steven@r-boc.com or Patrick@r-boc.com

bandctelcomproducts.com

720 N 17th Street, Unit 11, St. Charles, IL 60174

